



IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST]GEN FROM BALLABS TEST NO. 20685.0
 [TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC
 [ISSUE DATE] 04-16-2021
 [MANUFAC] WILLIAMS INDOOR
 [OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO 64836
 [LUMINAIRE] 1 BRIDGELUX V13 LED 4"RND RECESSED CAST HOUSING DOWNLIGHT
 [MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)
 [LUMCAT] 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS (EM MODE)
 [LAMPCAT] V13 BXRE-35E2000
 [_SEARCH_SOURCETYPE] LED
 [_SEARCH_APPLICATION] Indoor, Classroom, Commercial, Corridor, Hotel, Industrial, Office, Downlight
 [_SEARCH_MOUNTING] Recessed

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1136
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	114
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.22
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.37 ft (Diameter)
Luminous Width (90-270)	0.37 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	3445	3445	3445
55	1062	1062	1062
65	131	131	131
75	0	0	0
85	0	0	0

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES

CANDELA TABULATION

	<u>0</u>
0	974.945
5	1004.032
10	1034.196
15	1055.742
20	1102.604
25	1201.715
30	941.550
35	165.364
40	43.092
45	23.700
50	12.389
55	5.925
60	2.693
65	0.539
70	0.539
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT**PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	398.42	N.A.	35.10
0-30	911.34	N.A.	80.20
0-40	1109.12	N.A.	97.60
0-60	1134.75	N.A.	99.90
0-80	1135.95	N.A.	100.00
0-90	1135.95	N.A.	100.00
10-90	1039.38	N.A.	91.50
20-40	710.69	N.A.	62.60
20-50	730.35	N.A.	64.30
40-70	26.69	N.A.	2.30
60-80	1.20	N.A.	0.10
70-80	0.14	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1135.95	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	96.57
10-20	301.85
20-30	512.91
30-40	197.78
40-50	19.66
50-60	5.97
60-70	1.06
70-80	0.14
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102	101	100	98	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	77
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	66	61	57	66	60	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise


X=2H	Y=2H	0.4	0.4	0.4	0.4	0.4	UGR Viewed Endwise				
	3H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	4H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	6H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	8H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	12H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
4H	2H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	3H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	4H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	6H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	8H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	12H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
8H	4H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	6H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	8H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	12H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
12H	4H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	6H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
	8H	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4

Maximum UGR = 0.4

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L10-835-EM10W-DIM-UNV-OW-OF-CS_(EM MODE).IES

POLAR GRAPH



Maximum Candela = 1201.715 Located At Horizontal Angle = 0, Vertical Angle = 25

1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)