



IES INDOOR REPORT

PHOTOMETRIC FILENAME : 4DR-TL-L15-840-DIM-UNV-OW-OF-GD_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] GEN FROM BALLABS TEST NO. 20685.0

[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC

[ISSUEDATE] 15 APRIL 2020

[MANUFAC] WILLIAMS INDOOR

[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO

[LUMINAIRE] 4" RND RECESSED CAST HOUSING DOWNLIGHT

[MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)

[LUMCAT] 4DR-TL-L15-840-DIM-UNV-OW-OF-GD

[LAMPCAT] V13 BXRE-35E2000

[_SEARCH_SOURCETYPE] LED

[_SEARCH_APPLICATION] Indoor, Classroom, Commercial, Industrial, Office, Downlight

[_SEARCH_MOUNTING] Recessed

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1377
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	99
Total Luminaire Watts	13.9
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.22
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.37 ft (Diameter)
Luminous Width (90-270)	0.37 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4175	4175	4175
55	1287	1287	1287
65	159	159	159
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L15-840-DIM-UNV-OW-OF-GD_.IES

CANDELA TABULATION

	<u>0</u>
0	1181.778
5	1217.036
10	1253.599
15	1279.716
20	1336.519
25	1456.656
30	1141.297
35	200.445
40	52.233
45	28.728
50	15.017
55	7.182
60	3.265
65	0.653
70	0.653
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT**PHOTOMETRIC FILENAME : 4DR-TL-L15-840-DIM-UNV-OW-OF-GD_.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	482.95	N.A.	35.10
0-30	1104.67	N.A.	80.20
0-40	1344.41	N.A.	97.60
0-60	1375.48	N.A.	99.90
0-80	1376.94	N.A.	100.00
0-90	1376.94	N.A.	100.00
10-90	1259.88	N.A.	91.50
20-40	861.46	N.A.	62.60
20-50	885.29	N.A.	64.30
40-70	32.35	N.A.	2.30
60-80	1.45	N.A.	0.10
70-80	0.17	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1376.94	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	117.06
10-20	365.89
20-30	621.73
30-40	239.74
40-50	23.83
50-60	7.24
60-70	1.28
70-80	0.17
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L15-840-DIM-UNV-OW-OF-GD_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102	101	100	98	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	77
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	66	61	57	66	60	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52


IES INDOOR REPORT
PHOTOMETRIC FILENAME : 4DR-TL-L15-840-DIM-UNV-OW-OF-GD_.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	3H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	4H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	6H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	8H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	12H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
4H	2H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	3H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	4H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	6H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	8H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	12H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
8H	4H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	6H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	8H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	12H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
12H	4H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	6H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	8H	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1

Maximum UGR = 1.1

POLAR GRAPH



Maximum Candela = 1456.656 Located At Horizontal Angle = 0, Vertical Angle = 25
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)