


BALLABS CERTIFIED TEST REPORT NO.: 20410.0 DATE 05/24/18  
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
DESCRIPTION: GEN7 V13 LED 6"SHORT HEATSINK 6"RND ADJ DOWNLIGHT @ 0 TILT  
ACRYLIC MED TIR OPTIC & 6"WHITE ASYM TRIM w/ANGLED SOLITE  
LENS ADVANCE #XI025C070V054DSM5 @ 530mA  
CATALOG NBR: 6AR-L20/835-DIM-UNV-A-M-OF-WH (0 DEGREE TILT)  
LAMP TYPE : BXRE-35E2000

0 DEGREE PLANE CONTAINS MAXIMUM CANDLEPOWER



NVLAP LAB CODE 200921-0

LUMEN SUMMARY							
ZONE	LUMENS	%LAMP	%FIXT	ZONE	LUMENS	%LAMP	%FIXT
0- 30	1604.	NA.	90.2	90-120	0.	NA.	.0
0- 40	1709.	NA.	96.0	90-130	0.	NA.	.0
0- 60	1766.	NA.	99.3	90-150	0.	NA.	.0
0- 90	1779.	NA.	100.0	90-180	0.	NA.	.0
TOTAL LUMINAIRE =				0-180	1779.	NA.	100.0

THIS BALLABS REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY THIS CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.

SIGNIFICANCE OF THE TEST IS LIMITED TO THE DEGREE THAT THE TESTED SAMPLE IS REPRESENTATIVE. OTHER FACTORS AFFECT FIELD PERFORMANCE.

BALLABS CERTIFIED TEST REPORT NO.: 20410.0 DATE 05/24/18  
 PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
 DESCRIPTION: GEN7 V13 LED 6"SHORT HEATSINK 6"RND ADJ DOWNLIGHT @ 0 TILT  
 ACRYLIC MED TIR OPTIC & 6"WHITE ASYM TRIM w/ANGLED SOLITE  
 LENS ADVANCE #XI025C070V054DSM5 @ 530mA  
 CATALOG NBR: 6AR-L20/835-DIM-UNV-A-M-OF-WH (0 DEGREE TILT)  
 LAMP TYPE : BXRE-35E2000

CANDLEPOWER DISTRIBUTION  
 0 DEGREE PLANE CONTAINS MAXIMUM CANDLEPOWER

VERT	HORIZONTAL										LUMENS	
	.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0	FRONT	BACK	TOTAL
0	5230.	5230.	5230.	5230.	5230.	5230.	5230.	5230.	5230.			
5	5087.	5092.	5070.	5039.	4945.	4892.	4816.	4703.	4678.	241.8	229.0	470.7
10	4403.	4362.	4368.	4333.	4248.	4059.	3879.	3724.	3588.			
15	3091.	3136.	3122.	3055.	2905.	2702.	2516.	2363.	2274.	438.7	358.9	797.7
20	1670.	1753.	1755.	1655.	1544.	1382.	1323.	1268.	1220.			
25	798.	836.	795.	759.	718.	665.	657.	641.	638.	184.6	151.2	335.8
30	359.	380.	360.	331.	324.	333.	331.	333.	336.			
35	173.	175.	170.	159.	153.	156.	167.	177.	174.	52.5	52.3	104.8
40	85.	90.	88.	81.	82.	82.	90.	94.	94.			
45	42.	44.	44.	44.	47.	49.	52.	54.	54.	17.2	19.8	37.0
50	25.	27.	28.	31.	32.	32.	32.	36.	36.			
55	21.	22.	23.	24.	22.	21.	21.	22.	24.	10.4	9.7	20.1
60	19.	19.	21.	19.	17.	14.	12.	13.	13.			
65	16.	15.	15.	13.	8.	6.	6.	3.	3.	6.8	2.4	9.2
70	14.	15.	14.	9.	6.	3.	3.	2.	3.			
75	11.	9.	8.	5.	3.	1.	0.	0.	1.	3.9	.3	4.2
80	4.	4.	3.	1.	0.	0.	0.	0.	0.			
85	1.	0.	0.	0.	0.	0.	0.	0.	0.	.0	.0	.0
90	0.	0.	0.	0.	0.	0.	0.	0.	0.			

USE .500 FT. AS LENGTH AND .500 FT. AS WIDTH

BALLABS CERTIFIED TEST REPORT NO.: 20410.0 DATE 05/24/18  
 PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
 DESCRIPTION: GEN7 V13 LED 6"SHORT HEATSINK 6"RND ADJ DOWNLIGHT @ 0 TILT  
 ACRYLIC MED TIR OPTIC & 6"WHITE ASYM TRIM w/ANGLED SOLITE  
 LENS ADVANCE #XI025C070V054DSM5 @ 530mA  
 CATALOG NBR: 6AR-L20/835-DIM-UNV-A-M-OF-WH (0 DEGREE TILT)  
 LAMP TYPE : BXRE-35E2000

# ZONAL CAVITY COEFFICIENTS OF UTILIZATION

EFFECTIVE FLOOR CAVITY REFLECTANCE=.20

CEILING	.80		.70		.50		.30		.10		.00							
WALL	.70	.50	.30	.10	.70	.50	.30	.10	.50	.30	.10	.50	.30	.10	.50	.30	.10	.00
RCR																		
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.15	1.13	1.11	1.09	1.13	1.11	1.09	1.08	1.07	1.06	1.04	1.03	1.02	1.01	1.00	.99	.98	.97
2	1.11	1.07	1.03	1.01	1.09	1.05	1.02	1.00	1.02	1.00	.97	.99	.97	.95	.96	.95	.94	.92
3	1.07	1.02	.98	.95	1.05	1.01	.97	.94	.98	.95	.93	.96	.93	.91	.94	.92	.90	.89
4	1.03	.97	.93	.89	1.01	.96	.92	.89	.94	.91	.88	.92	.89	.87	.90	.88	.86	.85
5	.99	.93	.88	.85	.98	.92	.88	.84	.90	.87	.84	.89	.86	.83	.87	.85	.82	.81
6	.96	.89	.85	.82	.95	.89	.84	.81	.87	.84	.81	.86	.83	.80	.85	.82	.80	.79
7	.93	.86	.81	.78	.92	.85	.81	.78	.84	.80	.78	.83	.80	.77	.82	.79	.77	.76
8	.90	.83	.78	.75	.89	.82	.78	.75	.81	.77	.75	.80	.77	.74	.79	.76	.74	.73
9	.87	.79	.75	.72	.86	.79	.75	.72	.78	.74	.71	.77	.74	.71	.76	.73	.71	.70
10	.83	.76	.71	.68	.82	.75	.71	.68	.75	.71	.68	.74	.70	.68	.73	.70	.68	.67

TESTED IN ACCORDANCE WITH CURRENT IES PROCEDURES

BALLABS CERTIFIED TEST REPORT NO.: 20410.0 DATE 05/24/18  
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
DESCRIPTION: GEN7 V13 LED 6"SHORT HEATSINK 6"RND ADJ DOWNLIGHT @ 0 TILT  
ACRYLIC MED TIR OPTIC & 6"WHITE ASYM TRIM w/ANGLED SOLITE  
LENS ADVANCE #XI025C070V054DSM5 @ 530mA  
CATALOG NBR: 6AR-L20/835-DIM-UNV-A-M-OF-WH (0 DEGREE TILT)  
LAMP TYPE : BXRE-35E2000

\*\*\*\*\*

ELECTRICAL CHARACTERISTICS 120.00V .1798A 21.2950W

LUMINOUS EFFICACY (LUMENS / WATTS) = 83.6

TESTED IN ACCORDANCE WITH CURRENT IES STANDARDS  
UTILIZING ABSOLUTE PHOTOMETRY PER LM-79-08

