



IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] GEN FROM ATAL011609
[TESTLAB] ATAL-LABS
[ISSUE DATE] 08 OCT 2024
[MANUFAC] WILLIAMS INDOOR
[OTHER] H.E. WILLIAMS, INC. - CARTHAGE, MO.
[LUMCAT] 8DR-L60-830-DIM-UNV-OM-CS
[LUMINAIRE] 8.5 INCH ROUND, RECESSED LED DOWNLIGHT
[MORE] W/CLEAR SEMI-SPECULAR REFLECTOR
[LAMPCAT] BRIDGELUX VERO COB
[LAMP] (1) 3000K LED MODULE
[SEARCH_SOURCETYPE] LED
[SEARCH_APPLICATION] Indoor, Downlight
[SEARCH_MOUNTING] Recessed

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5824
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	81
Total Luminaire Watts	71.9
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.78
Spacing Criterion (90-270)	0.78
Spacing Criterion (Diagonal)	0.74
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.71 ft (Diameter)
Luminous Width (90-270)	0.71 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6961	6961	6961
55	232	232	232
65	175	175	175
75	114	114	114
85	170	170	170

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

CANDELA TABULATION

	<u>0</u>
0.0	9086.459
2.5	9110.834
5.0	9100.000
7.5	8678.042
10.0	8756.584
12.5	8146.667
15.0	7511.292
17.5	6791.959
20.0	5935.042
22.5	5045.625
25.0	4045.167
27.5	3215.875
30.0	2521.458
32.5	1842.208
35.0	1320.042
37.5	922.458
40.0	589.875
42.5	343.417
45.0	180.375
47.5	67.167
50.0	16.792
52.5	8.125
55.0	4.875
57.5	4.333
60.0	3.792
62.5	3.250
65.0	2.708
67.5	2.167
70.0	1.625
72.5	1.625
75.0	1.083
77.5	1.083
80.0	0.542
82.5	0.542
85.0	0.542
87.5	0.000
90.0	0.000
92.5	0.000
95.0	0.000
97.5	0.000
100.0	0.000
102.5	0.000
105.0	0.000
107.5	0.000
110.0	0.000
112.5	0.000
115.0	0.000
117.5	0.000
120.0	0.000
122.5	0.000
125.0	0.000
127.5	0.000
130.0	0.000
132.5	0.000

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

CANDELA TABULATION - (Cont.)

135.0	0.000
137.5	0.000
140.0	0.000
142.5	0.000
145.0	0.000
147.5	0.000
150.0	0.000
152.5	0.000
155.0	0.000
157.5	0.000
160.0	0.000
162.5	0.000
165.0	0.000
167.5	0.000
170.0	0.000
172.5	0.000
175.0	0.000
177.5	0.000
180.0	0.000

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	2917.94	N.A.	50.10
0-30	4783.72	N.A.	82.10
0-40	5646.31	N.A.	97.00
0-60	5819.57	N.A.	99.90
0-80	5823.53	N.A.	100.00
0-90	5823.9	N.A.	100.00
10-90	4977.42	N.A.	85.50
20-40	2728.37	N.A.	46.80
20-50	2895.53	N.A.	49.70
40-70	175.93	N.A.	3.00
60-80	3.96	N.A.	0.10
70-80	1.29	N.A.	0.00
80-90	0.37	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	5823.9	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	846.48
10-20	2071.46
20-30	1865.78
30-40	862.59
40-50	167.15
50-60	6.10
60-70	2.67
70-80	1.29
80-90	0.37
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	102	100	99	98	97	96	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89
3	104	98	94	90	102	97	93	90	95	91	88	92	89	87	90	88	86	84
4	100	93	88	84	98	92	87	84	90	86	83	88	84	82	86	83	81	79
5	95	88	83	79	94	87	82	78	85	81	78	84	80	77	82	79	76	75
6	91	83	78	74	90	82	77	74	81	76	73	80	76	73	78	75	72	71
7	87	79	73	70	86	78	73	69	77	72	69	76	72	69	75	71	68	67
8	84	75	70	66	82	74	69	66	73	69	65	72	68	65	71	68	65	64
9	80	71	66	62	79	71	66	62	70	65	62	69	65	62	68	65	62	60
10	77	68	63	59	76	68	63	59	67	62	59	66	62	59	65	62	59	58


IES INDOOR REPORT
PHOTOMETRIC FILENAME : 8DR-L60-830-DIM-UNV-OM-CS_.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	3H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	4H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	6H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	8H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	12H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
4H	2H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	3H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	4H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	6H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	8H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	12H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
8H	4H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	6H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	8H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	12H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
12H	4H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	6H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2
	8H	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2

Maximum UGR = 6.2

POLAR GRAPH



Maximum Candela = 9110.834 Located At Horizontal Angle = 0, Vertical Angle = 2.5
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)